

I) IN THE CLAIMS

1-22 (Cancelled).

23. (Previously presented) A wall bracket for supporting a loudspeaker and comprising:

a wall plate arranged for attachment to a home wall, the wall plate having a pair of raised flanges, one at each side thereof, projecting laterally outwards therefrom;

upper and lower bracket base members defining grooves arranged to slide onto said flanges and defining substantially hemispherical sockets and being constructed to embrace said wall plate;

a bracket mount comprising a mounting ball and a bracket arranged for attachment to the loudspeaker, the mounting ball having similar radius to the hemispherical sockets and being arranged for being captured and gripped therebetween and being pierced by a slot therethrough; and

a bolt deployable through the sockets and the slot in the mounting ball to clamp the upper and lower base members together around both the wall plate and the mounting ball, the slot being arranged to permit the bracket mount to be held in a variety of inclinations with respect to the wall plate.

24. (Currently amended) A wall bracket as claimed in claim 4 23 and having a grub screw and wherein the all plate has an upper flange arranged for the grub screw to screw therein, the upper bracket base member being so pierced as to enable the grub screw to lock said upper base member to said wall plate.

25. (New) A wall bracket as claimed in claim 23 and wherein the flanges are in parallel array.

26. (New) A wall bracket as claimed in claim 23 and wherein said upper and lower bracket base members have interfitting members whereby said bracket base members can be manually held together, with the ball in place, while the wall

bracket is assembled.

27. (New) A wall bracket as claimed in claim 23 and wherein said bolt has an enlarged head to enable it to be finger tightened.

28. (New) A wall bracket as claimed in claim 24 and wherein said bracket mount has a concave mounting surface, whereby it is adapted for holding a body with curved or flat rear or side surfaces.

29. (New) A wall bracket as claimed in claim 23 and wherein said bracket mount has two mounting saddles, one normal to the other, whereby it is adapted to carry a body with curved or flat rear or side surfaces.

30. (New) A wall bracket as claimed in claim 23 and wherein said bracket mount incorporates holes or slots for attachment of the body.

31. (New) A wall bracket as claimed in claim 23 and wherein the wall plate defines a cable management hole wherethrough cabling for the body can be routed.

32. (New) A wall bracket as claimed in claim 23 and adapted for use in a domestic context.

33. (New) Use of a wall bracket according to claim 23 in a home theatre or home cinema context.